# Data sheet Compression spring : D-380

GUTEKUNST FEDERN

05.2024

| | | |
|---|---|---|
| d | mm | Wire diameter |
| D | mm | Mean coil diameter |
| Dd | mm | Diameter of mandrel |
| De | mm | Outer coil diameter |
| Dh | mm | Diameter of bush |
| e1 | mm | Perm.dev. perpendicular line |
| e2 | mm | Perm.dev. parallel line |
| F1 | N | Prestressed spring force |
| F2 | N | Loaded spring force |
| Fn | N | Maximum force in static use |
| Fc | N | Theoretic maximum force at Lc |
| L0 | mm | Length of unstressed spring |
| L1 | mm | Prestressed spring length |
| L2 | mm | Loaded spring length |
| Lk | mm | Buckling length |
| Ln | mm | Minimum length in static use |
| Lc | mm | Block length |
| n | pc. | Aktive coils |
| nt | pc. | Total coils |
| R | N/mm | Spring rate |
| S | mm | Pitch (distance between coils) |
| s1 | mm | Prestressed spring deflection |
| s2 | mm | Loaded spring deflection |
| sh | mm | Maximum stroke in static use |
| sn | mm | Maximum spring deflection in static use |
| Weight | g | Weight of one spring in grammes |
| Fndyn | N | Maximum force in dynamic force |
| Fndtol | N | (+/-) tolerance of maximum dynamic force |
| Lndyn | mm | Minimum length in dynamic use |
| shdyn | mm | Maximum stroke in dynamic use |

* The spring data for the dynamic applications is relevant only for springs having a shot peened hardened surface !




n 3,50 | nt | R 71,644 | Weight 170,304

Spring test acc. to DIN ISO 2859/1 test level II

**1 Coiling direction**

☐ left ☒ right

**2 Dynamic load ***

| | |
|---|---|
| Fndyn | 1435,75 |
| Fndtol | 107,00 |
| Lndyn | 39,96 |
| shdyn | 9,29 |

**3 Excursion sh** mm

**4 Stress cyc. end. N**

**5 Stress cycle frequ. n** /

**6 Application temp.** °C

**7 Guidance and seat to DIN EN 13906-1**

☐ mandrel ☐ bush

Buckling length **Lk** at

v=0,5 / Bild 5 0,00 mm



**8 Material**

EN 10270-1

**9 Wire or rod surface**

☒ drawn ☐ rolled ☐ metal-cut

**10 Springs deburred** ☐ inside ☐ outside

**11 Surface treatment** ☐ shot peened

**12 Tolerances to DIN EN 15800**

| Grade | De,Di,D | L0 | F1,F2 | e1,e2 | Wire diameter **d** to DIN 2076 |
|---|---|---|---|---|---|
| 1 | ☐ | ☐ | ☐ | ☐ | |
| **2** | ☒ | ☒ | ☒ | ☒ | |
| 3 | ☐ | ☐ | ☐ | ☐ | ☒ |

**13 Prouction compensation through**

| | | |
|---|---|---|
| A spring resistance and associated length of tensed spring | L0 | ☐ |
| A spring resistance, associated length of tensed spring and L0 | n, d | ☒ |
| | n, De, Di | ☐ |
| Two spring resistances and associated lengths of tensed spring | L0, n, d | ☐ |
| | L0,n,De,Di | ☐ |

**14 Setting springs**

All springs which show setting tendency because of their size are pre-set within the production process.

**Prices**

| Mennyiségi lépcsk | Egységár (EUR) |
|---|---|
| 1 | 12,7100 € |
| 2 | 10,1200 € |
| 3 | 5,6200 € |
| 7 | 3,4700 € |
| 17 | 2,1700 € |
| 37 | 1,8100 € |
| 75 | 1,7400 € |
| 125 | 1,7063 € |
| 175 | 1,7081 € |
| 250 | 1,6746 € |
| 350 | 1,6471 € |

**Remarks**

Származási ország: DE | Vámtarifaszám: 73202081


**Gutekunst + Co.KG Spring Factories · Carl-Zeiss-Straße 15 · D-72555 Metzingen**

Sales +49 7123 960-192 · Customize springs +49 7123 960-193 · Main +49 7123 960-0

Fax +49 7123 960-195 · E-mail: order@gutekunst-co.com